

CUSTOMIZED CONTROLLER

BOD Laminar



BOD CARD



LAMINAR CARD

	Temperature: 0-50°C	
Input	RTD: PT-100, 3 Wire	Air Flow Sensor
	Heating + Cooling	Fan Speed : High / Low / Medium, UV, Light
Output	5 Relay Output	7 Relay Output
Accuracy	± 0.5% of FS	
Display	16 x 2 Jumbo LCD Display	20 x 4 LCD Display
Keyboard	4 Keys	10 Keys
Mounting	Card Form	
	230 VAC ± 10%, 50 HZ	
Environment	Temp : 0 - 50°C / Rh : 35 - 85 % (Non - Condensation)	



PLC-961



TIMER + RPM CARD




TEMP. CONTROLLER CARD

Case Size	96 x 96		
	92 x 92		
Range Limit	0-400°C	9999 Sec. / 4-5000 RPM	0-1200°C
Input	RTD: PT-100	Proximity Sensor	TC / RTD Universal
Function	Sock Timer / Perging Start-Stop	Timer / RPM	Heating / Cooling / BOD / COD
Accuracy	± 0.5% of FS		
Display	16 x 2 LCD Display	4 Digit Dual Display	
Keyboard	4 Keys		
Mounting	Card Form		
Power Supply	230 VAC ± 10%, 50 HZ		85-270 VAC / 50 Hz
Environment	Temp : 0 - 50°C / Rh : 35 - 85 % (Non - Condensation)		

THJ

Heat Press / Fusing Controller

Input	J/K type Thermocouple / Start pulse for Timer
Output	30 Amp for Heater, Relay for Pneumatic cylinder, Buzzer for job complete
Control	PID / On-Off Action
Range	0-999 Sec. Timer / 0-999 Count
Display	4 Digit Dual Display (THJ-610), O-LED high Bright (THJ-600)
Mounting	Card type PCB mounting
Supply	AC-85-265 V, 50 Hz



THJ-610