

## PLC



**HPC-14P12R3T**



**HPC-12P8R**

<b>Processor</b>	32 bit multitasking processor	
<b>Program Capacity</b>	32 Kb	16 Kb
<b>Execution Speed</b>	< 0.2 MicroSec	
<b>Data Register</b>	8 K Words	
<b>Program Download</b>	USB / COM PORT	
<b>Serial Port</b>	Serial Port Modbus RTU (Master / Slave configurable Mode) baud rate up to 115.2 Kbps	
<b>I/O's</b>	14*DI / 12*DO / 3-CH Temp ( 29 Point )	
<b>DI</b>	( NPN Type )	12*DI / 8*DO ( 20 Point )
<b>DO</b>	Relay or Transistor, Relay : 3 Amp / 230 VAC	
<b>TEMP</b>	3 CH T/C	None
<b>Shell Color</b>	Grey	
<b>Shell Material</b>	ABS	
<b>Mounting</b>	Channel Mounting	
<b>Dimension</b>	95 x 120 x 80 mm	95 x 85 x 80 mm
	H x W x D	
<b>Power Supply</b>	24 VDC	
<b>Power Consumption</b>	> 3 W	
<b>Working Environment</b>	Temp : 0 -50*C / RH : 35 - 85 % ( Non- Condensation )	
<b>Protection</b>	IP-65 ( Front Panel )	



**HPC-Extension**